



## HEB-Breitflanschträger / HEB-Wide flanged beams

HEB	Höhe	Breite	Steg	Flansch	Widerstandsmoment	Trägheitsmoment	Handelsgewicht
	Height	Width	Web	Flange	Section modulus	Moment of inertia	Commercial weight
	h	b	s	t	$W_x$	$I_y$	
	[mm]	[mm]	[mm]	[mm]	[cm <sup>3</sup> /m]	[cm <sup>4</sup> /m]	[kg/m]
100	100	100	6,0	10,0	90	450	20,9
120	120	120	6,5	11,0	144	864	27,4
140	140	140	7,0	12,0	216	1.509	34,5
160	160	160	8,0	13,0	311	2.492	43,7
180	180	180	8,5	14,0	426	3.831	52,5
200	200	200	9,0	15,0	570	5.696	63,0
220	220	220	9,5	16,0	736	8.091	73,0
240	240	240	10,0	17,0	938	11.259	85,0
260	260	260	10,0	17,5	1.150	14.919	95,0
280	280	280	10,5	18,0	1.380	19.270	106,0
300	300	300	11,0	19,0	1.680	25.166	120,0
320	320	300	11,5	20,5	1.930	30.824	130,0
340	340	300	12,0	21,5	2.160	36.656	137,0
360	360	300	12,5	22,5	2.400	43.193	146,0
400	400	300	13,5	24,0	2.880	57.680	159,0
450	450	300	14,0	26,0	3.550	79.888	175,0
500	500	300	14,5	28,0	4.290	107.176	192,0
550	550	300	15,0	29,0	4.970	136.691	204,0
600	600	300	15,5	30,0	5.700	171.041	217,0